

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A multi-functional peripheral comprising a printer configured to reduce volatile memory usage by loading individual software components, the multi-functional peripheral comprising:

a processor;

volatile memory in electronic communication with the processor;

non-volatile memory in electronic communication with the processor, the non-volatile

memory including an operating system, a loader application, a plurality of

individual software components, and a loading table that is directly configurable

by a user to control which of the individual software components are loaded into

volatile memory in connection with starting the operating system;

instructions stored in the non-volatile memory that are executable by the processor for

implementing a method comprising:

loading the operating system for the multi-functional peripheral comprising a

printer into the volatile memory;

starting the operating system;

loading the loader application into the volatile memory;

starting the loader application;

examining the loading table to determine which of the individual software

components are to be loaded into the volatile memory in connection with

starting the operating system; and

individually loading each of the individual software components that are to be

loaded as indicated in the loading table into the volatile memory in

connection with starting the operating system.

2. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the multi-functional peripheral is a printer/fax/copier.
3. (Cancelled)
4. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, further comprising an input component in electronic communication with the processor for a user to enter user input and thereby configure the loading table.
5. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 4, further comprising a display in electronic communication with the processor that displays information to the user relating to the loading table.
6. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 5, further configured with a menu structure that may be navigated by a user using the input component and the display to configure the loading table.
7. (Cancelled)
8. (Cancelled)
9. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the loading table is a license table comprising a list of licenses relating to the individual software components.
10. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 9, wherein the individual software components with licenses, as indicated by the license table, are loaded into the volatile memory.

11. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the volatile memory is RAM.
12. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the individual software components are software libraries.
13. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, further comprising:
 - a communications module in electronic communication with the processor for communications with a computer; and
 - a web interface accessible by a user through use of a web browser to configure the loading table.
14. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 13, wherein the web interface comprises a web page.
15. (Previously Presented) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the method further comprises:
 - examining hardware configuration by the loader application; and
 - modifying the loading table based on the hardware configuration.

16. (Currently Amended) A computer-readable medium for carrying program data, wherein the program data comprises executable instructions for implementing a method comprising:
- loading an operating system for a multi-functional peripheral comprising a printer into volatile memory;
 - starting the operating system;
 - loading a loader application into the volatile memory;
 - starting the loader application;
 - examining a loading table that is directly configurable by a user to determine which individual software components are to be loaded into the volatile memory in connection with starting the operating system; and
 - individually loading each of the individual software components that are to be loaded as indicated in the loading table into the volatile memory in connection with starting the operating system.
17. (Previously Presented) The computer-readable medium as defined in claim 16, wherein the multi-functional peripheral comprising a printer is a printer/fax/copier.
18. (Original) The computer-readable medium as defined in claim 16, further comprising a user configuring the loading table.
19. (Original) The computer-readable medium as defined in claim 18, further comprising providing a user interface to the user for configuring the loading table.
20. (Original) The computer-readable medium as defined in claim 19, wherein the user interface includes a menu structure that may be navigated by the user to configure the loading table.

21. (Cancelled)

22. (Cancelled)

23. (Original) The computer-readable medium as defined in claim 16, wherein the loading table is a license table comprising a list of licenses relating to the individual software components.

24. (Original) The computer-readable medium as defined in claim 23, wherein the individual software components with licenses, as indicated by the license table, are loaded into the volatile memory.

25. (Original) The computer-readable medium as defined in claim 16, wherein the volatile memory is RAM.

26. (Original) The computer-readable medium as defined in claim 16, wherein the individual software components are software libraries.

27. (Original) The computer-readable medium as defined in claim 16, further comprising providing a web interface accessible by a user through use of a web browser to configure the loading table.

28. (Original) The computer-readable medium as defined in claim 27, wherein the web interface comprises a web page.

29. (Original) The computer-readable medium as defined in claim 16, further comprising: examining hardware configuration by the loader application; and modifying the loading table based on the hardware configuration.

30. (Currently Amended) A method for reducing volatile memory usage in a multi-functional peripheral comprising a printer by loading individual software components, the method comprising:

loading an operating system for a multi-functional peripheral comprising a printer into volatile memory;

starting the operating system;

loading a loader application into the volatile memory;

starting the loader application;

examining a loading table that is directly configurable by a user to determine which individual software components are to be loaded into the volatile memory in connection with starting the operating system; and

individually loading each of the individual software components that are to be loaded as indicated in the loading table into the volatile memory in connection with starting the operating system.

31. (Previously Presented) The method as defined in claim 30, wherein the multi-functional peripheral comprising a printer is a printer/fax/copier.

32. (Cancelled)

33. (Previously Presented) The method as defined in claim 30, further comprising providing a user interface to the user for configuring the loading table.

34. (Original) The method as defined in claim 33, wherein the user interface includes a menu structure that may be navigated by the user to configure the loading table.

35. (Cancelled)

36. (Cancelled)

37. (Original) The method as defined in claim 30, wherein the loading table is a license table comprising a list of licenses relating to the individual software components.

38. (Original) The method as defined in claim 37, wherein the individual software components with licenses, as indicated by the license table, are loaded into the volatile memory.

39. (Original) The method as defined in claim 30, wherein the volatile memory is RAM.

40. (Original) The method as defined in claim 30, wherein the individual software components are software libraries.

41. (Original) The method as defined in claim 30, further comprising providing a web interface accessible by a user through use of a web browser to configure the loading table.

42. (Original) The method as defined in claim 41, wherein the web interface comprises a web page.

43. (Original) The method as defined in claim 30, further comprising:
examining hardware configuration by the loader application; and
modifying the loading table based on the hardware configuration.

44. (New) The multi-functional peripheral comprising a printer as defined in claim 1, wherein the individual software components are loaded into volatile memory after starting the operating system.

45. (New) The computer-readable medium as defined in claim 16, wherein the individual software components are to be loaded into the volatile memory after starting the operating system.

46. (New) The method as defined in claim 30, wherein the individual software components are to be loaded into the volatile memory after starting the operating system.